

SOURCE-LINE* Forestry Hose

Description

A very durable untreated single jacket forestry hose, rated with a service test pressure of 300 psi (20.7 bar), and constructed of 100% spun polyester lined with TPU elastomer. Supplied with NST aluminum couplings. The 1 1/2 in. (38 mm) size SOURCE-LINE* meets USDA FSS 5100-187 TYPE 1.

Specifications

Hose size	Coupling bowl size	Weight per 50 ft (15.2 m)	Coil		Service test pressure
			diameter per 50 ft (15.2 m)	diameter per 50 ft (15.2 m)	
1 in. (25 mm)	1 3/16 in. (30.2 mm)	4.2 lb (2 kg)	11 in. (28 cm)	11 in. (28 cm)	600 psi (41.4 bar)
1 1/2 in. (38 mm)	1 11/16 in. (42.9 mm)	6.6 lb (3 kg)	11 in. (28 cm)	11 in. (28 cm)	600 psi (41.4 bar)



010316

Ordering Information

Send queries to Williams Fire & Hazard Control for specific color and length combinations. Minimum order quantities may apply.

Note: The converted values in this document are provided for dimensional reference only and do not reflect an actual measurement.

* SOURCE-LINE is a trademark of Niedner.

WILLIAMS FIRE & HAZARD CONTROL and the product names listed in this material are marks and/or registered marks. Unauthorized use is strictly prohibited.